



SC Simplex Connector:
 SC multimode and single mode connector kits comprise of a one piece SC body with precision ceramic ferrule, crimp, sleeve, colour coded outer shroud, 2 x colour coded 3mm strain relief boots and a 0.9mm boot.
 Compliant with IEC60874-14
 Typical Insertion Loss:
 MM - 0.2dB, SM - 0.15dB
 Minimum Return Loss:
 SM 45dB



SC Simplex Adaptor:
 SC Adaptors comprise of a polymer outer body and inner assembly fitted with a precision alignment sleeve.
 Multimode with metal sleeve.
 Single mode with Ceramic Sleeve.
 Compliant with IEC 60875-14
 Max. Insertion Loss:
 MM - 0.3dB, SM - 0.1dB



SC Duplex Connector:
 SC Duplex connector kits comprise of 2 simplex connectors mounted in a two piece polymer clip and 2 x colour coded 3mm strain relief boots.
 Compliant with IEC 60874-14
 Typical Insertion Loss:
 MM - 0.2dB, SM - 0.15dB
 Minimum Return Loss:
 SM 45dB



SC Duplex Adaptor:
 SC Duplex adaptors comprise of a polymer outer body and an inner assembly fitted with a precision alignment sleeve.
 Multimode with metal sleeve.
 Single mode with Ceramic Sleeve.
 Compliant with IEC 60875-14
 Max. Insertion Loss:
 MM - 0.3dB, SM - 0.1dB

Brand-Rex Optical Components - Connectors

SC Optical Connectors

Product Part Numbering

	Connector	Adaptor
SC - MultiMode (Beige)	FOCSCEPMM001	BHCSCMM001
SC - Single Mode (Blue)	FOCSCEPSM001	BHCSCSM001
SC Duplex - Multi Mode (Beige)	FOCDCEPMM001	BHCDCMM001
SC Duplex - Single Mode (Blue)	FOCDCEPSM001	BHCDCSM001

SC Duplex Clip - Multi Mode (Beige)	FOCSCKLBE
SC Duplex Clip - Single Mode (Blue)	FOCSCKLBU